

아날로그 타이머

TTS 시리즈



1 Part

릴레이 & 소켓

단상용 MC

릴레이 터미널

아날로그 타이머

SSR

온도 조절기

터치 스크린

형명구분도

TTS	- B	1	2	
1 시간 설정 범위	0.5S/5S/30S/3M 60S/10M/60M/6H ☞ S : Sec M : Min H : Hour	1S/10S/60S/6M 2M/20M/2H/12H	5S/50S/5M/30M 4M/40M/4H/24H	10S/100S/10M/60M
2 전원 전압	220VAC	110VAC	24VDC	110VDC

성능 및 사양


반복오차율	최대 ±0.5
리셋타임	최대 100ms
점점구성	2C, 5A 240VAC (저항부하)
소비전력	DC : 1.2W
	AC : 2VA
내전압	1,500VAC 1분간
수명	기계적 최소 1,000,000
	전기적 최소 200,000
사용전압	220VAC, 110VAC, 24VDC, 110VDC (정격전압의 ±10%이내)
사용주위온도	-25°C ~ +55°C

☞ 제품의 사양 및 재질은 품질향상 등의 목적으로 예고없이 변경될 수 있습니다.

아날로그 타이머



TTS 시리즈

제품구분도


	시간설정범위	품명			
		220VAC	110VAC	110VDC	24VDC
	0.5	TTS-B0.5S 220VAC	TTS-B0.5S 110VAC	TTS-B0.5S 110VDC	TTS-B0.5S 24VDC
	5S	TTS-B005S 220VAC	TTS-B005S 110VAC	TTS-B005S 110VDC	TTS-B005S 24VDC
	30S	TTS-B030S 220VAC	TTS-B030S 110VAC	TTS-B030S 110VDC	TTS-B030S 24VDC
	3M	TTS-B003M 220VAC	TTS-B003M 110VAC	TTS-B003M 110VDC	TTS-B003M 24VDC
	1S	TTS-B001S 220VAC	TTS-B001S 110VAC	TTS-B001S 110VDC	TTS-B001S 24VDC
	10S	TTS-B010S 220VAC	TTS-B010S 110VAC	TTS-B010S 110VDC	TTS-B010S 24VDC
	60S	TTS-B060S 220VAC	TTS-B060S 110VAC	TTS-B060S 110VDC	TTS-B060S 24VDC
	6M	TTS-B006M 220VAC	TTS-B006M 110VAC	TTS-B006M 110VDC	TTS-B006M 24VDC
	5S	TTS-B005S 220VAC	TTS-B005S 110VAC	TTS-B005S 110VDC	TTS-B005S 24VDC
	50S	TTS-B050S 220VAC	TTS-B050S 110VAC	TTS-B050S 110VDC	TTS-B050S 24VDC
	5M	TTS-B005M 220VAC	TTS-B005M 110VAC	TTS-B005M 110VDC	TTS-B005M 24VDC
	30M	TTS-B030M 220VAC	TTS-B030M 110VAC	TTS-B030M 110VDC	TTS-B030M 24VDC
10S	TTS-B010S 220VAC	TTS-B010S 110VAC	TTS-B010S 110VDC	TTS-B010S 24VDC	
100S	TTS-B100S 220VAC	TTS-B100S 110VAC	TTS-B100S 110VDC	TTS-B100S 24VDC	
10M	TTS-B010M 220VAC	TTS-B010M 110VAC	TTS-B010M 110VDC	TTS-B010M 24VDC	
60M	TTS-B060M 220VAC	TTS-B060M 110VAC	TTS-B060M 110VDC	TTS-B060M 24VDC	
60S	TTS-B060S 220VAC	TTS-B060S 110VAC	TTS-B060S 110VDC	TTS-B060S 24VDC	
10M	TTS-B010M 220VAC	TTS-B010M 110VAC	TTS-B010M 110VDC	TTS-B010M 24VDC	
60M	TTS-B060M 220VAC	TTS-B060M 110VAC	TTS-B060M 110VDC	TTS-B060M 24VDC	
6H	TTS-B006H 220VAC	TTS-B006H 110VAC	TTS-B006H 110VDC	TTS-B006H 24VDC	
2M	TTS-B002M 220VAC	TTS-B002M 110VAC	TTS-B002M 110VDC	TTS-B002M 24VDC	
20M	TTS-B020M 220VAC	TTS-B020M 110VAC	TTS-B020M 110VDC	TTS-B020M 24VDC	
2H	TTS-B002H 220VAC	TTS-B002H 110VAC	TTS-B002H 110VDC	TTS-B002H 24VDC	
12H	TTS-B012H 220VAC	TTS-B012H 110VAC	TTS-B012H 110VDC	TTS-B012H 24VDC	
4M	TTS-B004M 220VAC	TTS-B004M 110VAC	TTS-B004M 110VDC	TTS-B004M 24VDC	
40M	TTS-B040M 220VAC	TTS-B040M 110VAC	TTS-B040M 110VDC	TTS-B040M 24VDC	
4H	TTS-B004H 220VAC	TTS-B004H 110VAC	TTS-B004H 110VDC	TTS-B004H 24VDC	
24H	TTS-B024H 220VAC	TTS-B024H 110VAC	TTS-B024H 110VDC	TTS-B024H 24VDC	

외형치수도, 접속도, 출력 동작


단위 : mm



CONNECTION



TIME CHART



소켓

KF083A

KPZ2

