

# 아날로그 타이머

TTM 시리즈



## 형명구분도

TTM - ① ② ③

① 시간 설정 범위	0.5 : 0.5	001 : 1	180 : 180(Sec 전용)	
	005 : 5	010 : 10	030 : 30	060 : 60
② 시간 단위	S : Sec	M : Min		
③ 전원 전압	110VAC	220VAC	12VDC	24VDC

## 성능 및 사양

반복오차율	최대 ±1%
리셋타임	최대 100ms
접점구성	4C, 3A 240VAC (저항부하)
소비전력	DC : 1.2W
	AC : 2VA
내전압	1,500VAC 1분간
수명	기계적 최소 1,000,000
	전기적 최소 200,000
사용전압	220VAC 50/60 Hz, 110VAC 50/60 Hz, 24VDC, 12VDC
사용주위온도	-25°C ~ +55°C (단, 결빙되지 않는 상태)

※ 제품의 사양 및 재질은 품질향상 등의 목적으로 예고없이 변경될 수 있습니다.

## 제품구분도





접점사양	시간 단위	시간 설정 범위	품명			
			220VAC	110VAC	24VDC	12VDC
4C	SEC	0.5	TTM-40.5S 220VAC	TTM-40.5S 110VAC	TTM-40.5S 24VDC	TTM-40.5S 12VDC
		1	TTM-4001S 220VAC	TTM-4001S 110VAC	TTM-4001S 24VDC	TTM-4001S 12VDC
		5	TTM-4005S 220VAC	TTM-4005S 110VAC	TTM-4005S 24VDC	TTM-4005S 12VDC
		10	TTM-4010S 220VAC	TTM-4010S 110VAC	TTM-4010S 24VDC	TTM-4010S 12VDC
		30	TTM-4030S 220VAC	TTM-4030S 110VAC	TTM-4030S 24VDC	TTM-4030S 12VDC
		60	TTM-4060S 220VAC	TTM-4060S 110VAC	TTM-4060S 24VDC	TTM-4060S 12VDC
4C	MIN	180	TTM-4180S 220VAC	TTM-4180S 110VAC	TTM-4180S 24VDC	TTM-4180S 12VDC
		5	TTM-4005M 220VAC	TTM-4005M 110VAC	TTM-4005M 24VDC	TTM-4005M 12VDC
		10	TTM-4010M 220VAC	TTM-4010M 110VAC	TTM-4010M 24VDC	TTM-4010M 12VDC
		30	TTM-4030M 220VAC	TTM-4030M 110VAC	TTM-4030M 24VDC	TTM-4030M 12VDC
		60	TTM-4060M 220VAC	TTM-4060M 110VAC	TTM-4060M 24VDC	TTM-4060M 12VDC



## 외형치수도, 접속도, 출력 동작

단위 : mm

## 소켓



## KMY4

## KMY4S

