



# LINE SEIKI

## Digital Thermometer



# TC-3200

### General Specification

<b>Height of Digit</b>	Main: 14mm Sub: 7mm
<b>Number of Input</b>	2
<b>Sensor</b>	Thermocouple K type or J type (Sold Separately)
<b>Sampling Time of Display</b>	Approx. 1 second
<b>Sampling Time of Data Logger</b>	1 to 3600 seconds or Manual
<b>Data Logging Number</b>	1600 points
<b>Communication</b>	RS-232 PC Serial Interface
<b>Operating Temp./Humidity</b>	0 to 50 °C / Less than 80%RH
<b>Power Supply</b>	006P type battery
<b>Dimensions</b>	135 (H) x 60 (W) x 33 (D) (mm)
<b>Weight</b>	Approx. 165 g (Battery included.)
<b>Accessories</b>	Instruction Manual, Battery
<b>Compliance</b>	CE, RoHS

### Accuracy

<b>Resolution</b>	0.1 °C
<b>Range</b>	K: -199.9 to +1,300.0 °C J: -199.9 to +1,100.0 °C
<b>Accuracy</b>	Range: -199.9 to -50.1 °C Accuracy: ± (0.4% +1°C) Range: -50.0 to +1,300.0 (+1,100) °C Accuracy: ± (0.4% +0.8°C)

- Two Channel Thermometer
- Data Logger Function
- Real-Time Measurement Function
- Data Hold
- Max./Min. Record



## Line Seiki Co., Ltd.

## WWW.LINESEIKI.COM

37-7, Chuo-Cho, 2-Chome, Meguro-Ku, Tokyo Japan 152-0001  
 Please visit our company website for contact details  
 E-Mail: webtrade@line.co.jp