







제어용 스위치 악세서리

Ø16, 19, 20

옵션

구분 및 형상	사용 홀치수 & 전압	색상	모델	T	적용 시리즈				
					Ø16 K	Ø16 F	Ø16 M	Ø20 매입형 K	Ø20 매입형 F
투명 보호 커버  <p>☞ T□ -C 보호 커버는 PL / PB / PBL만 적용 가능합니다.</p>	Ø16	투명	T16-C	○	-	-	-	-	-
	Ø19	투명	T19-C	○	-	-	-	-	-
	Ø22	투명	T22-C	○	-	-	-	○	○
정사각 보호커버 - 박스형 	Ø16	□ : 무표시(흑색) R(적색) G(녹색) Y(황색)	K16-S111□	○	○	-	-	-	-
직사각 보호커버 - 박스형 	Ø16	□ : 무표시(흑색) R(적색) G(녹색) Y(황색)	K16-S112□	○	○	-	-	-	-
정사각 보호커버 - 사이드 오픈/ 스프링형 	Ø16		K16-S221	○	○	-	-	-	-
직사각 보호커버 - 사이드 오픈/ 스프링형 	Ø16		K16-S222	○	○	-	-	-	-
보호 가드 	Ø16	황색	K16-G1	-	○	○ (EPB 제외)	-	-	-
보호 가드 	Ø16	황색	K16-G2	-	○	○ (EPB 제외)	-	-	-
LED 	24V AC/DC 12V AC/DC 6V AC/DC	□ : R(적색) G(녹색) Y(황색) W(백색) B(청색)	-	-	K16-S115□	-	-	K16-S115□	-
	24V AC/DC 12V AC/DC 6V AC/DC	□ : R(적색) G(녹색) Y(황색) W(백색) B(청색)	-	-	-	F16-S115□	-	-	F16-S115□

접선

구분 및 형상	사용 홀치수 & 전압	색상	모델	T	적용 시리즈				
					Ø16 K	Ø16 F	Ø16 M	Ø20 매입형 K	Ø20 매입형 F
220VAC 트랜스 	220VAC	흑색	-	-	-	F16-T1	-	-	F16-T1
Ø16 Hole Cover 	Ø16	흑색	K16-S117	○	○	○	○	-	-
고정링 조임공구 	-	흑색	K16-W1	-	○	○	-	○	○
LED 교환공구 	-	흑색	K16-LR1	-	○	-	-	○	-
소켓 (Soldering) 	-	흑색	K16-S113	○	○	-	-	○	-
소켓 (PCB) 	-	흑색	K16-S114	○	○	-	-	○	-
접점블럭 1N/O + 1N/C 		흑색	FCB	-	-	○	-	-	○
공블럭 		흑색	FEB	-	-	○	-	-	○
단자 보호커버 			F16-S116	○	-	○	-	-	○
커넥터 	Ø16	흑색	T16-S07 T16-S11 T16-S21 T16-S17 T16-S27	○	-	-	-	-	-
	Ø19, Ø22 (겸용)	흑색	T19-S07 T19-S11 T19-S17 T19-D11 T19-D21 T19-D17 T19-D27	○	-	-	-	-	-

Ø22

Ø25








Ø30

도면

제어용 스위치 악세서리

Ø22, 25, 30용 보호가커버 & 가드

옵션

구분 및 형상	사용 출치수	색상	모델	J2	T	적용 시리즈							
						Ø25 매입형 K25F	Ø30 매입형 K30F	Ø25 AL가드 K25F-AL	K22-91	K	B	KEX	
투명 보호커버 <small>※ T□ -C 보호커버는 PL / PB / PBL만 적용 가능 합니다.</small>		Ø22	투명	T22-C	-	○	-	-	-	-	-	-	-
		Ø25	투명	T25-C	-	○	○	-	-	-	-	-	-
		Ø30	투명	T30-C	-	○	-	○	-	-	-	-	-
보호커버 <small>(30.2X35.3X18.7)</small>		Ø22	-	SC2	-	-	-	-	-	-	○	-	-
		Ø25	-	SC5	-	-	-	-	-	-	○	○	-
보호커버 <small>(KSC12 Ø35.4X 30.9 KSC15 Ø35.4X 30.9 KSC13 Ø39.6X 30.4)</small>		Ø22	흑색	KSC12	-	-	-	-	-	-	○	-	-
		Ø25	흑색	KSC15	-	-	-	-	-	-	○	○	-
		Ø30	흑색	KSC13	-	-	-	-	-	-	○	○	-
원형방수커버 Ø40 플러그드용 <small>(Ø50.2x26.3)</small>		Ø22 Ø25 Ø30		HP100	-	-	-	-	-	-	○	○	-
방진, 방유, 방수커버 Ø65용 <small>Ø80x35 (Ø65용 방진/방유/방수커버)</small>		Ø22 Ø25 Ø30	□ :	HP120□	-	-	-	-	-	-	○	○	-
			R(적색) G(녹색) Y(황색) B(청색) K(흑색) W(백색)										
원형방수커버 <small>(Ø31x16.5)</small>		Ø25		RCR	-	-	-	-	-	-	○	-	-
사각방수커버 <small>(31x31x16.5)</small>		Ø25		RCS	-	-	-	-	-	-	○	-	-

Ø16

Ø19

Ø20








범용선

구분 및 형상	사용 출치수	색상	모델	J2	T	적용 시리즈							
						Ø25 매입형 K25F	Ø30 매입형 K30F	Ø25 AL가드 K25F-AL	K22-91	K	B	KEX	
 (65x81x39)	Ø22	□ : Y(황색)	KEG12 □	○	○	-	-	-	○	○	-	-	Ø22 Ø25 Ø30
	Ø25	R(적색) G(녹색)	KEG15 □	-	-	○	-	○	-	○	○	-	
	Ø30	A(호박색) W(백색)	KEG13 □	-	-	-	○	-	-	○	○	-	
보호커버  (Ø55x74x37.5) ※ KEX 비상, 가드, 명판 타입제외	Ø22	□ : R(적색)	KEG32 □	-	○	-	-	-	-	○	-	○	도면
	Ø25	Y(황색) G(청색)	KEG35 □	-	-	○	-	○	-	○	○	-	
	Ø30	K(흑색) C(투명)	KEG33 □	-	-	-	○	-	-	○	○	-	
 (Ø49.5x69x32) (EPB/MPB제외) ※ KEX 비상, 가드, 명판 타입제외	Ø22		KEG42	○	○	-	-	-	-	○	-	○	
	Ø25	투명	KEG45	-	-	○	-	○	-	○	○	-	
	Ø30		KEG43	-	-	-	○	-	-	○	○	-	

제어용 스위치 악세서리

Ø22, 25, 30용 명판 & 박스









옵션

구분 및 형상	사용 홀치수	색상	모델	J2	T	적용 시리즈						
						Ø25 매입형 K25F	Ø30 매입형 K30F	Ø25 AL가드 K25F-AL	K22-91	K	B	KEX
 (Ø99 H40.8)	Ø22	황색	KEG72	○	○	-	-	-	○	○	-	-
	Ø25		KEG75	-	-	-	-	-	-	○	○	-
	Ø30		KEG73	-	-	-	-	-	-	○	○	-
 (Ø99 H40.8)	Ø22	백색	KEG72W	○	○	-	-	-	○	○	-	-
	Ø25		KEG75W	-	-	-	-	-	-	○	○	-
	Ø30		KEG73W	-	-	-	-	-	-	○	○	-
 (Ø90 H39.1)	Ø22	황색	KEG82	○	○	-	-	-	○	○	-	-
	Ø25		KEG85	-	-	-	-	-	-	○	○	-
	Ø30		KEG83	-	-	-	-	-	-	○	○	-
 (Ø90 H39.1)	Ø22	백색	KEG82W	○	○	-	-	-	○	○	-	-
	Ø25		KEG85W	-	-	-	-	-	-	○	○	-
	Ø30		KEG83W	-	-	-	-	-	-	○	○	-
 (Ø90 H38.8)	Ø22	황색	KEG92	○	○	-	-	-	○	○	-	-
	Ø25		KEG95	-	-	-	-	-	-	○	○	-
	Ø30		KEG93	-	-	-	-	-	-	○	○	-
 (Ø90 H38.8)	Ø22	백색	KEG92W	○	○	-	-	-	○	○	-	-
	Ø25		KEG95W	-	-	-	-	-	-	○	○	-
	Ø30		KEG93W	-	-	-	-	-	-	○	○	-
	Ø22	황색	KEG82YL-△	○	○	-	-	-	○	○	-	-
	Ø25		KEG85YL-△	-	-	-	-	-	-	○	○	-
	Ø30		KEG83YL-△	-	-	-	-	-	-	○	○	-

※ △ - 회로방식 : N(NPN), P(PNP)
 ※ KEG7,8,9는 HP119 시리즈와 결합이 가능합니다.
 - 사용예



범선

구분 및 형상	사용 출치수	색상	모델	J2	T	적용 시리즈							
						Ø25 매입형 K25F	Ø30 매입형 K30F	Ø25 AL가드 K25F-AL	K22-91	K	B	KEX	
이중화 보호가드	 (76.5X65X43)	황색	KEG-12C	○	○	-	-	-	○	○	-	-	
			KEG-15C	-	-	○	-	○	-	○	○	-	
			KEG-13C	-	-	-	○	-	-	○	○	-	
	 (Ø99 H45)	황색	KEG-72C	○	○	-	-	-	○	○	-	-	
			KEG-75C	-	-	-	-	-	○	○	-		
			KEG-73C	-	-	-	-	-	○	○	-		
	 (Ø90 H43)	황색	KEG-82C	○	○	-	-	-	○	○	-	-	
			KEG-85C	-	-	-	-	-	○	○	-		
			KEG-83C	-	-	-	-	-	○	○	-		
명판	 (30X40.5X6.3)	흑색	HP110A	-	-	-	-	-	-	○	-	-	
			HP110B	-	-	-	-	-	-	○	-	-	
	 (Ø60 t=2.6mm)	제품 : 황색 글자 : 흑색	HP111A	-	-	-	-	-	-	○	-	-	
			HP111B	-	-	-	-	-	-	○	-	-	
			HP111C	-	-	-	-	-	-	○	-	-	
	 (Ø75 t=2.8mm)	제품 : 황색 글자 : 흑색	HP112A	-	-	-	-	-	-	○	-	-	
			HP112B	-	-	-	-	-	-	○	-	-	
			HP112C	-	-	-	-	-	-	○	-	-	
	 (Ø70 t=1mm H=10mm)	제품 : 황색 글자 : 흑색	HP117A	-	-	-	-	-	-	○	○	-	-
			HP117B	-	-	-	-	-	-	-	○	-	-
			HP117C	-	-	-	-	-	-	-	○	-	-
	 (Ø80 t=1mm H=10mm)	제품 : 황색 글자 : 흑색	HP118A	-	-	-	-	-	-	○	○	-	-
HP118B			-	-	-	-	-	-	-	○	-	-	
HP118C			-	-	-	-	-	-	-	○	-	-	

* 주의 : 이중화 보호가드의 지지대를 커팅 하지 않으면 비상정지 스위치는 눌러지지 않습니다.

Ø22

Ø25




Ø30

도면

제어용 스위치 약세서리


Ø22, 25, 30

옵션

구분 및 형상	사용 홀치수 & 전압	색상	모델	적용 시리즈											
				J2	T	Ø25 매입형 K25F	Ø30 매입형 K30F	Ø25 AL가드 K25F-AL	K22-91	K	B	KEX			
 <p>(62 x 48.5 t=0.2mm)</p>	Ø22	제품 : 황색 글자 : 흑색	HP119E												
			HP119K	○	-	-	-	-	○	○	○	-			
			HP119C												
	Ø25	제품 : 황색 글자 : 적색	HP119E-R	○	-	-	-	-	-	○	○	○	-		
			공용	제품 : 백색 글자 : 흑색	HP119E- W(STOP)	○	-	-	-	-	○	○	○	-	
				제품 : 백색 글자 : 적색	HP119E- W(STOP-R)	○	-	-	-	-	○	○	○	-	
	명판	Ø22	제품 : 황색 글자 : 흑색	HP119E(OFF)	○	-	-	-	-	○	○	○	-		
				Ø25	제품 : 황색 글자 : 적색	HP119E(OFF-R)	○	-	-	-	-	○	○	○	-
						공용	제품 : 백색 글자 : 흑색	HP119E-W(OFF)	○	-	-	-	-	○	○
				제품 : 백색 글자 : 적색	HP119E- W(OFF-R)		○	-	-	-	-	○	○	○	-
	 <p>(Ø62 t=0.2mm)</p>	Ø22	제품 : 황색 글자 : 흑색	HP119E-1(STOP)	○	-	-	-	-	○	○	-	-		
				Ø25	제품 : 백색 글자 : 흑색	HP119E- 1W(STOP)	○	-	-	-	-	○	○	-	-
공용		제품 : 황색 글자 : 적색	HP119E- 1(STOP-R)			○	-	-	-	-	○	○	-	-	
		제품 : 백색 글자 : 흑색	HP119E- 1(OFF)	○	-	-	-	-	○	○	-	-			
 <p>(Ø62 t=0.2mm)</p>	Ø22	제품 : 황색 글자 : 흑색	HP119E-1(OFF)	○	-	-	-	-	○	○	-	-			
			Ø25	제품 : 황색 글자 : 적색	HP119E- 1(OFF-R)	○	-	-	-	-	○	○	-	-	
	공용	제품 : 백색 글자 : 흑색			HP119E- 1W(OFF)	○	-	-	-	-	○	○	-	-	
		제품 : 백색 글자 : 적색	HP119E- 1W(OFF)	○	-	-	-	-	○	○	-	-			
박스	Ø22	황색	KEX-101Y	○	-	-	-	-	○ (1A+1B 까지, 좌우 2 접점까지)	○ (비조광, 1A+1B 까지)	-	-			

※KEX-101Y는 HP119 시리즈와 결합이 가능합니다.

- 사용예











Ø16

Ø19

단위선

단위 : mm

Ø20

구분 및 형상	사양	모델	J2	T	적용 시리즈						
					Ø25 매입형 K25F	Ø30 매입형 K30F	Ø25 AL가드 K25F-AL	K22-91	K	B	KEX
		CBA	-	-	○	○	○	○	○	-	-
		J2-10	○	-	-	-	-	-	-	-	-
1NO 접점		BCA (일반용) BCA-G (비상용)	-	-	-	-	-	-	-	○	-
		KEX-CB10	-	-	-	-	-	-	-	-	○
	 ※ IEC60947-5-1 직접개로동작방식	CBB	-	-	-	○	○	○	○	-	-
		J2-01	○	-	-	-	-	-	-	-	-
1NC 접점		BCB (일반용) BCB-G (비상용)	-	-	-	-	-	-	-	○	-
		KEX-CB01	-	-	-	-	-	-	-	-	○

Ø22

Ø25

Ø30













도면

제어용 스위치 악세서리

Ø22, 25, 30

옵션

단위 : mm

구분 및 형상	사양	모델	J2	T	적용 시리즈						
					Ø25 매입형 K25F	Ø30 매입형 K30F	Ø25 AL가드 K25F-AL	K22-91	K	B	KEX
2NO 접점	 	J2-S20	○	-	-	-	-	-	-	-	-
	 	CBA2	-	-	0	0	0	0	0	-	-
2NC 접점	 	J2-S20	○	-	-	-	-	-	-	-	-
	  <p>※ IEC60947-5-1 직접개로동작방식</p>	CBB2	-	-	0	0	0	0	0	-	-
1NO + 1NC	 	J2-S11	○	-	-	-	-	-	-	-	-
	  <p>※ IEC60947-5-1 직접개로동작방식</p>	CBC	-	-	0	0	0	0	0	-	-












필라멘트

구분 및 형상	사양	모델	J2	T	적용 시리즈						
					Ø25 매입형 K25F	Ø30 매입형 K30F	Ø25 AL가드 K25F-AL	K22-91	K	B	KEX
필라멘트	6.3V AC/DC (220VAC, 110VAC용)	BA7S (조광 선택터)	-	-	-	-	-	-	○	-	-
	24V AC/DC (24VDC용)	BA9S (조광 선택터 外)	-	-	-	-	-	-	○	-	-
	Ⓐ - 색상 : R(적색), G(녹색), Y(황색), B(청색), W(백색), K(흑색)	BA7S-KⒶ (조광 선택터)	-	-	-	-	-	-	○	-	-
	6.3V AC/DC (220VAC, 110VAC용) 24V AC/DC (24VDC용)	BA9S-KⒶ (조광 선택터 外)	-	-	-	-	-	-	○	-	-
LED	Ⓐ - 색상 : R(적색), G(녹색), Y(황색), B(청색), W(백색)	BA9S-JⒶ	○	-	-	-	-	-	-	-	-
	6V AC/DC, 12V AC/DC, 24V AC/DC, 110V AC/ DC, 220V AC/DC										
	Ⓐ - 색상 : R(적색), G(녹색), Y(황색), B(청색), W(백색), K(흑색)	BA9S-BⒶ	-	-	-	-	-	-	-	○	-
	24V AC/DC										
LED Trans	X1—⊗—X2										
	Ⓐ - 색상 : R(적색), G(녹색), Y(황색), B(청색), W(백색) 12/24VDC 110VDC 110/220VAC	KT-Ⓐ	-	-	○	○	○	-	-	-	-

제어용 스위치 악세서리

Ø22, 25, 30용 명판 & 박스

옵션

구분 및 형상	사양	모델	J2	T	Ø25 매입형 K25F	Ø30 매입형 K30F	적용 시리즈					
							Ø25 AL가드 K25F-AL	K22-91	K	B	KEX	
자기유지 Holder		KAL	-	-	○	○	○	-	○	-	-	
홀타입 접점안전커버		투명	KP-10	-	-	○	○	○	○	○	-	-
밀폐타입 접점안전커버		투명	KP-11	-	-	○	○	○	○	○	-	-
홀타입 트렌스 안전커버		투명	KP-20	-	-	○	○	○	○	○	-	-
밀폐타입 트렌스 안전커버		투명	KP-21	-	-	○	○	○	○	○	-	-
홀타입 접점안전커버 (CBA2,CBB2, CBC용)		투명	KP-30	-	-	○	○	○	○	○	-	-
밀폐타입 접점안전커버 (CBA2,CBB2, CBC용)		투명	KP-30	-	-	○	○	○	○	○	-	-
Ø19 커넥터		흑색	T19-S07 T19-S11 T19-S17	-	○	-	-	-	-	-	-	-
Ø19,Ø22 커넥터 (겸용)		흑색	T19-D11 T19-D21 T19-D17 T19-D27	-	○	-	-	-	-	-	-	-
Ø 22 커넥터		흑색	T22-S07 T22-S11 T22-S17	-	○	-	-	-	-	-	-	-
Ø 25, Ø 30 커넥터 (겸용)		흑색	T25-D07 T25-D11 T25-D21 T25-D17 T25-D27	-	○	-	-	-	-	-	-	-

Ø16

Ø19

Ø20

면선

구분 및 형상	사용 출치수	색상	모델	J2	T	적용 시리즈							
						Ø25 매입형 K25F	Ø30 매입형 K30F	Ø25 AL가드 K25F-AL	K22-91	K	B	KEX	
이중화 보호가드	 (76.5X65X43)	황색	KEG-12C	○	○	-	-	-	○	○	-	-	Ø22 Ø25 Ø30
			KEG-15C	-	-	○	-	○	-	○	○	-	
			KEG-13C	-	-	-	○	-	-	○	○	-	
	 (76.5X65X43)	백색	KEG-12C	○	○	-	-	-	○	○	-	-	Ø22 Ø25 Ø30
			KEG-15C	-	-	○	-	○	-	○	○	-	
			KEG-13C	-	-	-	○	-	-	○	○	-	
	 (Ø99 H45)	황색	KEG-72C	○	○	-	-	-	○	○	-	-	도면
			KEG-75C	-	-	-	-	-	-	○	○	-	
			KEG-73C	-	-	-	-	-	-	○	○	-	
 (Ø99 H45)		백색	KEG-72C	○	○	-	-	-	○	○	-	-	
			KEG-75C	-	-	-	-	-	-	○	○	-	
			KEG-73C	-	-	-	-	-	-	○	○	-	
 (Ø90 H43)	황색	KEG-82C	○	○	-	-	-	○	○	-	-		
		KEG-85C	-	-	-	-	-	-	○	○	-		
		KEG-83C	-	-	-	-	-	-	○	○	-		

표준

구분 및 형상	재질	색상	모델	적용 시리즈	
				KEG-1□C	KEG-7□C / KEG-8□C
 (Ø61.5X 45.5 t=0.2mm)		제품 : 황색 글자 : 흑색	HP-1CE(STOP)	○	-
 (Ø61.5X 45.5 t=0.2mm)		제품 : 황색 글자 : 적색	HP-1CE-R(STOP)	○	-
 (Ø77.6 t=0.2mm)		제품 : 황색 글자 : 흑색	HP-7CE(STOP)	-	○
 (Ø77.6 t=0.2mm)		제품 : 황색 글자 : 적색	HP-7CE-R(STOP)	-	○
이중화 보호가드용 명판	 (Ø61.5X 45.5 t=0.2mm)	제품 : 황색 글자 : 흑색	HP-1CE(OFF)	○	-
	 (Ø61.5X 45.5 t=0.2mm)	제품 : 황색 글자 : 적색	HP-1CE-R(OFF)	○	-
	 (Ø77.6 t=0.2mm)	제품 : 황색 글자 : 흑색	HP-7CE(OFF)	-	○
	 (Ø77.6 t=0.2mm)	제품 : 황색 글자 : 적색	HP-7CE-R(OFF)	-	○

※ 이중화 보호가드 설치 예



KEG-1□C + KEX-101Y 「스위치 박스와 이중화 보호가드 결합」
 KEG-1□C KEG-7□C KEG-8□C

제어용 스위치 악세서리

Ø16, 19, 20

Ø16


Ø19

외형치수도

단위 : mm

Ø20

T Series 보호커버




Model	A	B	C	D
T16-C	Ø16.5	Ø28.5	8.0	32.5
T19-C	Ø19.5	Ø28.5	8.0	32.5
T22-C	Ø22.5	Ø36.0	8.5	40.0
T25-C	Ø25.5	Ø36.0	8.5	40.0
T30-C	Ø30.5	Ø40.0	8.5	44.0

Ø22


Ø25

Ø30


K16 - S111




K16 - S112




K16 - S221




K16 - S222




K16 - G1




K16 - G2




K16 - S115




F16 - S115 / LED




K16 - S117




K16 - W1



K16 - LR1



K16 - S113




제어용 스위치 약세서리

Ø16, 19, 20


외형치수도

단위 : mm


F16 - T1 / 220VAC 트랜스




K16 - S114




FCB / 접점 블록 (1N/O + 1N/C)



FEB / 공블럭



F16 - S116 / Terminal Protection



제어용 스위치 약세서리

Ø22, 25, 30

Ø16


Ø19

외형치수도


단위 : mm

Ø20

SC2, SC5



Model	"A"
SC2	Ø22
SC5	Ø25



model	KSC12	KSC15	KSC13
B	Ø22	Ø25	Ø30
C	Ø31.0	Ø35.0	Ø42.0
D	Ø22	Ø25	Ø30
E	27.0	31.0	37.0
F	15.0	17.0	20.5

Ø22


Ø25

Ø30


KEG12 / 15 / 13

KEG32 / 35 / 33


KEG42 / 45 / 43



Model	"A"	Color
KEG12	Ø22	적색, Green Orange, Blue
KEG15	Ø25	
KEG13	Ø30	



Model	"A"	Color
KEG32	Ø22	적색, Green Orange, Blue Clear, 흑색(K)
KEG35	Ø25	
KEG33	Ø30	




Model	"A"	Color
KEG42	Ø22	적색, Green Orange, Blue Clear, 흑색(K)
KEG45	Ø25	
KEG43	Ø30	


HP110A / HP110B

HP117A / 117B / 117C


HP118A / 118B / 118C



A	HP110A Ø22
	HP110B Ø25



Model	"A"	Color
HP117A	Ø22	황색
HP117B	Ø25	
HP117C	Ø30	



Model	"A"	Color
HP118A	Ø22	황색
HP118B	Ø25	
HP118C	Ø30	


제어용 스위치 악세서리

Ø22, 25, 30

외형치수도


단위 : mm

KEG7 시리즈




Model	'A'
KEG72	Ø22
KEG75	Ø25
KEG73	Ø30

KEG8 시리즈




Model	'A'
KEG82	Ø22
KEG85	Ø25
KEG83	Ø30

KEG9 시리즈




Model	'A'
KEG92	Ø22
KEG95	Ø25
KEG93	Ø30


HP119E / HP119K / HP119C / HP119E-R




HP119E-1 시리즈




KEX-101Y



Top View



Bottom View



Side View

Ø16

Ø19

Ø20




외형치수도

단위 : mm

CBA / CBB

CBA2 / CBB2 / CBC




KT / 220VAC 트랜스



J2-10 / J2-01

J2-20 / J2-02 / J2-11








KAL / 자기유지 Holder



CBA, CBB용 접점안전커버

트랜스안전커버

CBA2 CBB2 CBC용 접점안전커버



도면


제어용 스위치 액세서리

Ø22, 25, 30


외형치수도

단위 : mm


BA7S




BA7S-K




BA9S




BA9S-K




BA9S-B



BA9S-J



HP100




HP111 & HP112




Model	"A"	"B"	"T"
HP111A	Ø22.2	Ø60	2.6
HP111B	Ø25.2	Ø60	2.6
HP111C	Ø30.1	Ø60	2.6
HP112A	Ø22.2	Ø75	2.8
HP112B	Ø25.2	Ø75	2.8
HP112C	Ø30.1	Ø75	2.8



HP120




RCR




RCS




KEX-101Y



Top View



Bottom View




Side View


외형치수도

단위 : mm


T16 커넥터




T19 커넥터



T22 커넥터



T25 커넥터



Ø16

Ø19

Ø20

Ø22



Ø25

Ø30

도면

KEG-1□C




KEG-1SC



KEG-7□C



KEG-8□C

KEG-7SC



HP-1CE Series

HP-7CE Series



제어용 스위치 약세서리

Ø22, 25, 30

Ø16



Ø19

Ø20

패널 가공도 및 패널부착 간격 치수

KEG7 시리즈

KEG8, KEG9 시리즈





Model	'A'	'B'	'C'
KEG82, 92	Ø22.5	3	10±0.2
KEG85, 95	Ø25.5	3	11±0.2
KEG83, 93	Ø30.5	3	13.5±0.2

KEG8□YL-△ 회로구성


구분	배선 방식	공통(com)	LED 그룹1	LED 그룹2	LED 그룹3
선 색상	+com	백(W)	적(R)	황(Y)	녹(G)
	-com	흑(K)	적(R)	황(Y)	녹(G)

※ □ - 사용홀치수 : 2(Ø22), 5(Ø25), 3(Ø30)
 △ - 회로방식 : N(NPN), P(PNP)

KEG8□YL-△ LED 회로구성



KEG8□YL-△ LED 그룹배치 회로구성



KEG8□YL-△ 회로 배선 예

